

40125

Nylon Scraper with Threaded Handle, 100 mm, White



Suitable for loosening stubborn dirt like pastry, chocolate, burnt on food, etc. on smooth surfaces. The nylon blade is a good alternative to a stainless steel blade and can be used on sensitive surfaces to avoid scratches on equipment and sensitive conveyor belts. The hard blade can withstand hot surfaces when used at intervals of max. 2 minutes at a time. Can be used with any Vikan handle.

Technical Data

Item Number	40125
Blade Thickness	2.7 mm
Material	Nylon Polypropylene
Recycling Symbol "7", Miscellaneous Plastics	Yes
Complies with (EC) 1935/2004 on food contact materials ¹	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation CFR 21	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Complies with REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
Phthalates and bisphenol A intentionally added	No
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x 180-200 cm)	3150 Pcs
Quantity Per Layer (Pallet)	150 Pcs.
Length	205 mm
Width	100 mm
Height	32 mm
Net Weight	0.07 kg
Weight bag (Recycling Symbol "4" Low Density Polyethylene (LDPE))	0.00402 kg
Weight cardboard (Recycling symbol "20" PAP)	0.006 kg
Tare total	0.01002 kg
Gross Weight	0.08 kg
Cubic metre	0.000656 M3
Recommended sterilisation temperature (Autoclave)	121 °C
Max. cleaning temperature (Dishwasher)	93 °C
Max usage temperature (food contact)	175 °C
Max usage temperature (non food contact)	175 °C
Min. usage temperature ³	-20 °C
Max. drying temperature	120 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH
Gtin-13 Number	5705020401251
GTIN-14 Number (Box quantity)	15705020401258
Customs Tariff No.	39241000

New equipment should be cleaned, disinfected, sterilised and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

3. Do not store the product below 0° Celsius.